

Model		HB7016T2
Housing		1.3U
Operation System		Embedded LINUX
Video	Compression	H.264
	Input	16ch BNC (1 Vp-p,75Ω)
	Output	1 BNC, 1 VGA
	Dual Stream	Support
Audio	Compression	G.711A
	Input	16ch BNC
	Output	1ch BNC
	Bidirectional Talk	1ch in, 1ch out(3.5mm MIC Interface)
Alarm	Input	16
	Output	2
Preview	Resolution	BNC : D1, 704x576(PAL)/704x480(NTSC) VGA: 1280x1024
	Display	1ch/ 4ch/ 9ch/ 16ch
	Sequence	Yes
	Privacy Masking	4 zones Maximum, On DVR
Recording	Resolution	16CIF/16D1 @6fps/ch
	Recording Mode	Manual, Schedule, Motion, Alarm
	Recording Quality	CBR, VBR
	Recording Interval	Pre-record: 5~30 sec., Post-record: 0~180sec.
Playback	Channel	CIF 16ch realtime; D1 16ch@6fps/ch
	Search Mode	Time, Date, Record Mode, Smart search
	Privacy Masking	4 zones Maximum, On DVR and PC
Network	Remote Operation	WEB(IE, Google, Firefox)
Email		Test and send
Mobile		Support (iPhone, Android, Ipad/ Windows Mobile, Symbian, BlackBerry)
Backup		USB devices & Network download
HDD		2xHDD, (2TB each)
External Interface	Network Interface	RJ45 10M/100M Ethernet Interface
	USB Interface	2 ports(Mouse control & Backup)
	Serial Interface	1 RS-485
General	Power Supply	220±30% V,50±3% Hz / 110±20% V,60±3% Hz
	Power Consumption	10W(Without HDD)
	Working Temperature	-10℃-45℃
	Dimension	324mm×245mm×47mm(W×D×H)
	Weight	4KG(without HDD)