

Model		HB7108X3-LH
Housing		1U
Operation System		Embedded LINUX
Video	Compression	H.264
	Input	8ch BNC (1.0 Vp-p,75Ω)
	Output	1 BNC, 1 VGA, 1 HDMI
	Dual Stream	Support
Audio	Compression	G.711A
	Input	2ch RCA
	Output	1ch RCA
	Bidirectional Talk	Support Multiplexing with audio input CH1
Alarm	Input	4
	Output	1
Preview	Resolution	BNC : D1, 704x576(PAL)/704x480(NTSC) VGA:1280X1024
	Display	1ch/ 4ch/ 8ch/ 9ch
	Sequence	Yes
	Privacy Masking	4 zones Maximum, On DVR
Recording	Resolution	8xFD1/CIF
	Recording Mode	Manual, Schedule, Motion, Alarm
	Recording Quality	CBR, VBR
	Recording Interval	Pre-record: 5~30 sec., Post-record: 0~180sec.
Playback	Channel	4ch Realtime
	Search Mode	Time, Date, Record Mode, Smart search, Quick Playback
	Privacy Masking	4 zones Maximum, On DVR and PC
Network	Remote Operation	WEB(IE, Google, Firefox)
Email		Test and send
Mobile		Support (IPhone, Android, Ipad)
Backup		USB devices & Network download
HDD		1HDD(Max support 2TB)
External Interface	Network Interface	RJ45 10M/100M Ethernet Interface
	USB Interface	2 ports(Mouse control & Backup)
	Serial Interface	1 RS-485 (HDX)
General	Power Supply	220±30% V,50±3% Hz / 110±20% V,60±3% Hz
	Power Consumption(Without HDD)	8W(Without HDD)
	Working Temperature	-10℃-45℃
	Dimension	254mm×168mm×45mm(W×D×H)
	Weight	1.5KG(without HDD)