

Model		HB7108X3
Housing		1U
Operation System		Embedded LINUX
Video	Compression	H.264
	Input	8ch BNC(1 Vp-p,75Ω)
	Output	1 BNC, 1 VGA,1 HDMI
	Dual Stream	Support
Audio	Compression	G.711A
	Input	2ch RCA(1KΩ,Vp-p=2.0V LINE)
	Output	1ch RCA(600Ω,Vp-p=2.0V LINE)
	Bidirectional Talk	3.5mm MIC Input Interface
Alarm	Input	4
	Output	1
Preview	Resolution	FD1: PAL(704×576), NTSC(704×480) 960H: PAL(928×576), NTSC(928×480) VGA : 1920*1080
	Display	1ch/ 4ch/ 8ch/ 9ch
	Sequence	Yes
	Privacy Masking	4 zones Maximum, On DVR
Recording	Resolution	8ch FD1/CIF/960H/Q960H
	Recording Mode	Manual, Schedule, Motion, Alarm
	Recording Quality	CBR, VBR
	Recording Interval	Pre-record: 5~30 sec., Post-record: 0~180sec.
Playback	Channel	8ch/16ch 960H Full Channels Realtime Playback
	Search Mode	Time, Date, Record Mode, Smart Search,Quick Playback
	Privacy Masking	4 zones Maximum, On DVR and PC
Network	Connection Way	Support 3G
	Remote Operation	WEB(IE, Chrome, Firefox, Safari)
Email		Test and send
Mobile		Support (IPhone, Android, Ipad)
Backup		USB devices & Network download
HDD		2 HDD(Max support 4TB each)
External Interface	Network Interface	1 RJ-45 10/100M/1000M adaptive Ethernet Interface
	USB Interface	2 Interfaces(Mouse control & Backup)
	Auxiliary Interface	1 RS-485(HDX)
General	Power Supply	220±30% V,50±3% Hz / 110±20% V,60±3% Hz
	Power Consumption(Full Load)	27W
	Working Environment	-10℃~+45℃ / 15%~85%RH
	Dimension	324mm×245mm×47mm(W×D×H)
	Weight	1.5KG(without HDD)